

**MORPAC  
INDUSTRIES**

## **M40 TRACKED DRILL**



We have the largest stock of new & used tracks in the northwest.

## **MORPAC INDUSTRIES, INC.**

117 Frontage Road North, Suite A  
Pacific, WA 98047-1052

Website: <http://www.morpac.com/>  
Email: [actuators@morpac.com](mailto:actuators@morpac.com)

Phone: (253) 735-8922  
Fax: (253) 735-8933

July 2007

# M40 TRACKED DRILL

- Standard M40 Morgan undercarriage with 23" wide tracks
- Cat C-9 270 hp engine
- Racor fuel filter water separator
- Electric starter with two 8-D 12 volt batteries
- Donaldson type two stage air filters
- Sullair 825 CFM @ 100 PSI rotary screw compressor or Ingersoll Rand 850 compressor
- New transfer drive (splitter box) with two air operated clutches providing full engine power to the compressor or transmission
- Fuller 1605 transmission for 9 forward speeds and two reverse
- Auxiliary air compressor to operate auxiliary controls
- Maxi brake pots which will stop the machine should the air compressor fail
- G226 differential
- ATD3800 boom with 5' extension for 22'8" maximum straight line drilling, with a 40 degree swing in each direction
- UFA chain feed for 12' steel with hydraulic scissor-style centralizer
- 3 gallon air line oiler
- 120 gallon detergent tank
- PR66 valveless drifter for 2 1/2" to 4" holes
- ROPS cab
- 2 heater fans and windshield wipers
- Bostrum air ride seat
- 2 working lights forward, 2 reverse

## Specifications

Weight approx.....57,000 lbs  
Width.....9 ft 11 in.  
Height (cradled).....13 ft 2 in.  
Height (shipping).....10 ft 8 in.  
Length (cradled).....26 ft 7 in.  
Electrical.....25 volt  
Ground clearance.....20 in.  
Ground pressure.....7.6 psi

## **MORPAC INDUSTRIES, INC.**

117 Frontage Road North, Suite A  
Pacific, WA 98047-1052

Website: <http://www.morpac.com/>  
Email: [actuators@morpac.com](mailto:actuators@morpac.com)

Phone:(253) 735-8922  
Fax: (253) 735-8933